Marble Conditioner

MIRACLE Sealants Company
www.miraclesealants.com

To Polish & Increase Slip Resistance For

- Marble
- Terrazzo
- Agglomerate
- Travertine
- Other Natural Stone

Uses

- Floors
- Counters
- Walls
- Stairs
- Ramps
- Showers

Special Features

- Removes Acid Etching
- Increases Polish
- Increases Slip Resistance
- Easy To Use
- Inexpensive
- Fast

PRODUCT DESCRIPTION

KEEP OUT OF REACH OF CHILDREN. Marble Conditioner is a chemical recrystallization treatment for use with marble, terrazzo, agglomerate, travertine and some granite. When used as part of a stone care program it will enhance the polished finish and make the surface harder and less slippery. **Marble Conditioner** is very effective as an ongoing maintenance procedure to maintain polish and slip resistance in high traffic areas.

Sample Testing

Due to the differences of each substrate, several inconspicuous test patches should be completed to assure maximum performance. **User must determine suitability of the product for their intended use.**

Protect Neighboring Surfaces

Always protect neighboring surfaces including wood, carpet, metal, landscaping and other masonry and non masonry surfaces.

APPLICATION INSTRUCTIONS

Read entire label and SDS/PDS before using. This product should be used directly from container and is not under any circumstances to be thinned or diluted with anything before use.

For the best performance and protection **Miracle Penetrating Sealer/ Impregnator** should be used as directed on all surfaces and grout before using **Marble Conditioner** or any other recrystallization formula. This will help resist darkening of light colored surfaces or grout lines. **Miracle Penetrating Sealer/Impregnator** will also provide water, stain and slip resistance.

Make sure the surface is completely dry before using.

Shake **Marble Conditioner** thoroughly and pour into a plastic trigger spray bottle. Once in spray bottle, shake contents frequently throughout operation. Spray lightly onto the surface being treated immediately buffing area with a **Marble Master MM1000** (175 rpm/150lbs.) floor machine equipped with a #0, #1 or #2 steel wool pad. Work areas approximately 3' x 3' in size. Apply 2 -3 squirts to the surface, working area in a side to side motion until dry. Once one side of the steel wool pad becomes dirty, turn it over and use the other side. When several sections are completed the overall area should be buffed one last time with a clean dry steel wool pad. This will remove any swirl marks that might be present. Make sure that the steel wool pads, are clean and dry. All steel wool shavings should be removed with a dry dust mop once the area has been completed. Check the finish in day light conditions for your final evaluation. Use **Marble Conditioner** as often as traffic dictates, monthly, quarterly, annually. In heavily damaged areas, honing the surface with abrasives may be necessary prior to the use of **Marble Conditioner** in order to achieve desired results.

Special Note: It is also recommended that surfaces be honed with abrasives periodically in order to break the surface crystals that build on the surface with prolonged use. This is important in allowing the proper vapor transmission necessary to natural stone surfaces.

Acid and the vapors, no matter how mild, may damage metal, carpet, leather, vinyl, wood and other surfaces. Take caution in transporting in original, upright and sealed container.

Heavy Duty Cleaning: For a non-acid deep clean, use **Liquid Poultice** as directed.

Light Duty Cleaning: Use **Tile & Stone Cleaner, Counter Kleen** or **Limestone/Travertine Soap** as directed.

Coverage

Coverage will vary depending on density, porosity, texture, surface absorption, weather, time solution left on surface and application methods. Used as directed, **Marble Conditioner** will cover approximately 1000 - 5000 square feet per gallon (90 - 455 square meters per 3.785 liters) depending on the surface.

MAINTENANCE

For ongoing maintenance instructions please refer to **Miracle Sealants Care Guide.** Refer to the **Miracle Sealants Product Recommendation Chart** for specific product recommendations.

Storage

Store **Marble Conditioner** in the original container, properly sealed to avoid contamination and evaporation. Stored at 77° F (25° C), **Marble Conditioner** will have a shelf life of 12 months. Do not allow to freeze.

Technical Support

For additional technical support, contact Miracle Sealants Company at 1-800-350-1901 or 626-443-6433 ext. 3013

Office Hours

Monday - Friday from 8:30 am - 5:00 pm PT.
1-626-443-6433 or 1-800-350-1901 • Fax: 1-626-443-1435
website: www.miraclesealants.com

Product Damaged During Transportation

If product is damaged during transportation contact
Info Trac @ 1-800-535-5053

Additional Products

Miracle Sealants Company offers a complete line of water & stain repellents, sealers, cleaner, polishing compounds, diamond abrasives, machinery and accessories for the tile, stone, concrete, metal, fabric and carpet professional or do-it yourself specialist.

Warranty

Instructions are a condensed guide and should not be considered complete. In the event of failure, the only obligation of Miracle Sealants Company shall be to replace such products proven to be defective. **Before using, user shall determine the suitability of the product for their intended use. User assumes all risks and liability whatsoever in connection therein.** Neither seller nor manufacturer shall be liable for any injury or inability to use this product.

Caution

Marble Conditioner contains silica fluorides. Open windows and use fans to circulate air. Good ventilation means that fresh air is flowing in such a way to feel a slight breeze. Avoid prolonged contact with skin. Chemical resistant gloves should be worn at all times. Keep small children and pets out of area until product or surface has thoroughly dried. **Refer to the SDS for additional information.**

11 - 2013